

FOCAL
SUSPENDED
W222S

Ceiling suspended luminaire; aluminium body and polycarbonate canopy; surface Pale green; PMMA lens and polycarbonate reflector; NCS S 2005-B50G; with COB (Chip on Board) technology for maximum efficiency; DALI Push dim; light colour 2700 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90; degree of protection IP20; Class 1; inclusive cable suspension max. 3000mm; light source replaceable by Wastberg+ or by a professional with explicit authorization; control gear not replaceable;







TECHNICAL INFORMATION

Physical	
Material	Lamp Body: Aluminium
IP Rating	IP20
Safety Class	Class I

LED	
Colour Rendering Index	CRI ≥ 90
Lumen Maintenance	L80 / 50000h
Macadam Ellipse	≤ 3 SDCM (initial MacAdam)

More technical information online

wastberg.com/en/products/focal-suspended-w222s

ARTICLE-SPECIFIC INFORMATION

Mounting	Ceiling
Luminous Flux	995 lm
Colour Temperature	2700 K
Optic	super wide flood
Control	DALI Push dim
Voltage	220 - 240 V
Power	10.5 W
Weight	0.7 kg

Colour / Finish	**Art. No. / EAN code**
Pale green	**222S101272** / 7330492000442

FOCAL
SUSPENDED
W222S

Wastberg AB
T +46 10 16 15 010
info@wastberg.com
wastberg.com

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The applicable General Terms & Conditions apply.