

ALMA
CEILING
W171C

Round ceiling surface luminaire made from aluminium; low-profile design; surface Signal white; RAL 9003; lamp socket E27; Phase-cut dim; light colour 2700 K; ≤ 6 SDCM (initial MacAdam); CRI ≥ 90; degree of protection IP20; Class 1; lamp included; compatible with most standard lighting tracks; light source replaceable by end-user;







TECHNICAL INFORMATION

Physical	
Material	Shade: Aluminium
IP Rating	IP20
Safety Class	Class I

LED	
Colour Rendering Index	CRI ≥ 90
Lumen Maintenance	L70 / 15000h
Macadam Ellipse	≤ 6 SDCM (initial MacAdam)

More technical information online

wastberg.com/en/products/alma-ceiling-w171c

ARTICLE-SPECIFIC INFORMATION

Mounting	Ceiling
Colour Temperature	2700 K
Control	Phase-cut dim
Voltage	220 - 240 V
Power	7.0 W
Weight	2.8 kg

Colour / Finish
Signal white

ALMA
CEILING
W171C

Art. No. / EAN code
171C10227 / 7330492007939

Wastberg AB
T +46 10 16 15 010
info@wastberg.com
wastberg.com

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The applicable General Terms & Conditions apply.