

CAST
SEMI-RECESSED
W261R

Ceiling semi-recessed luminaire; aluminium body; surface Anthracite; magnetic interchangeable lenses allow quick switching between three beam angles: 15°, 36° and 56°; with COB (Chip on Board) technology for maximum efficiency; Phase-cut dim; light colour 2700 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90; degree of protection IP20; Class 2; light source replaceable by Wastberg+ or by a professional with explicit authorization; control gear replaceable by end-user;







TECHNICAL INFORMATION

Physical	
Material	Lamp Body: Aluminium
IP Rating	IP20
Safety Class	Class II
LED	
Colour Rendering Index	CRI ≥ 90
Lumen Maintenance	L80 / 50000h
Macadam Ellipse	≤ 3 SDCM (initial MacAdam)

More technical information online

wastberg.com/en/products/cast-semi-recessed-w261r

ARTICLE-SPECIFIC INFORMATION

Mounting	Ceiling
Luminous Flux	1270 lm
Colour Temperature	2700 K
Optic	Narrow
Control	Phase-cut dim
Voltage	220-240 V
Power	10.1 W
Weight	0.6 kg

Colour / Finish	**Art. No. / EAN code**
Anthracite	**261R1127205** / 7330492018645

CAST
SEMI-RECESSED
W261R

Wastberg AB
T +46 10 16 15 010
info@wastberg.com
wastberg.com

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The applicable General Terms & Conditions apply.