




CAST
CEILING
W261C

Ceiling surface luminaire; aluminium body; surface Raw aluminium; magnetic interchangeable lenses allow quick switching between three beam angles: 15°, 36° and 56°; with COB (Chip on Board) technology for maximum efficiency; DALI Push dim; light colour 2700 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; degree of protection IP20; Class 2; light source replaceable by Wastberg+ or by a professional with explicit authorization; control gear replaceable by end-user;



56° 350° 90°

**TECHNICAL
INFORMATION**

Physical	
Material	Lamp Body: Aluminium
IP Rating	IP20
Safety Class	Class II
LED	
Colour Rendering Index	CRI ≥ 90
Lumen Maintenance	L80 / 50000h
Macadam Ellipse	≤ 3 SDCM (initial MacAdam)

More technical information online

wastberg.com/en/products/cast-ceiling-w261c



**ARTICLE-SPECIFIC
INFORMATION**

Mounting	
Luminous Flux	
Colour Temperature	
Optic	
Control	
Voltage	
Power	
Weight	
Colour / Finish	
Raw aluminium	

CAST
CEILING
W261C

Ceiling
1150 lm
2700 K
Flood
DALI Push dim
220-240 V
9.9 W
0.7 kg

Art. No. / EAN code

261C1227420 / 7330492018515